

Move Forward with

## **AUTOMATION**

# CONTROLS

# PROCESS

Move

Forward


with





© 2022 SMC Corporation of America, All Rights Reserved. All reasonable efforts to ensure the accuracy of the information detailed in this catalog were made at the time of publishing. However, SMC can in no way warrant the information herein contained as specifications are subject to change without notice.




A = Brass











# Inch Size One-Touch Fittings

### **Applicable Tubing-Inch, Thread-UNF, NPT**

[] Thread Material/Surface treatment N = Brass + Nickel Plated







KQ2H	L f M	ale Connector Jse to pipe a emale thread. Most general nodel.
Applicable tube O.D. [inch]	Connecting Thread	Model
1/8	10-32 UNF 1/16 1/8 1/4	KQ2H01-32 KQ2H01-33 KQ2H01-34 S KQ2H01-35 S
5/32	10-32 UNF 1/16 1/8 1/4	KQ2H03-32 KQ2H03-33 S KQ2H03-34 S KQ2H03-35 S
3/16	10-32 UNF 1/8 1/4	KQ2H05-32 KQ2H05-34 S KQ2H05-35 S
1/4	10-32 UNF 1/16 1/8 1/4 3/8	KQ2H07-32 KQ2H07-33 KQ2H07-34 S KQ2H07-35 KQ2H07-36 S
5/16	1/8 1/4 3/8	KQ2H09-34 - S KQ2H09-35 - S KQ2H09-36 - S
3/8	1/8 1/4 3/8 1/2	KQ2H11-34 B KQ2H11-35 B KQ2H11-36 B KQ2H11-37 B
1/2	1/4 3/8 1/2	KQ2H13-35 S KQ2H13-36 S KQ2H13-37 S




[inch]	Threau	
1/8	10-32 UNF	KQ2K01-32□
1/0	1/8	KQ2K01-34 - S
5/32	10-32 UNF	KQ2K03-32□
0/02	1/8	KQ2K03-34 🗆 S
3/16	1/8	KQ2K05-34 - S
	10-32 UNF	KQ2K07-32□
1/4	1/8	KQ2K07-34 ¤S
1/4	1/4	KQ2K07-35 🛛 S
	3/8	KQ2K07-36 🛛 S
	1/8	KQ2K09-34 🛛 S
5/16	1/4	KQ2K09-35 🛛 S
	3/8	KQ2K09-36 🛛 S
	1/8	KQ2K11-34 🛛 S
3/8	1/4	KQ2K11-35 🛛 S
5/6	3/8	KQ2K11-36 🛛 S
	1/2	KQ2K11-37 🛛 S
	1/4	KQ2K13-35 S
1/2	3/8	KQ2K13-36 S
	1/2	KQ2K13-37 🛛 S


		Reducer Elbow se to change the ube direction from one-touch fittings y 90° and to educe size.
Applicable tube O.D. [inch]	Applicable Fitting Size	Model
1/8	5/32 3/16	KQ2L01-03A
	1/4	KQ2L01-05A KQ2L01-07A
5/32	<mark>1/4</mark> 3/16 1/4	KQ2L01-07A KQ2L03-05A KQ2L03-07A
5/32 3/16	1/4 3/16 1/4 1/4 5/16	KQ2L01-07A KQ2L03-05A KQ2L03-07A KQ2L05-07A KQ2L05-09A
	1/4 3/16 1/4 1/4 5/16 5/16 3/8	KQ2L01-07A KQ2L03-05A KQ2L03-07A KQ2L05-07A KQ2L05-09A KQ2L07-09A KQ2L07-11A
3/16	1/4 3/16 1/4 1/4 5/16 5/16	KQ2L01-07A KQ2L03-05A KQ2L03-07A KQ2L05-07A KQ2L05-09A KQ2L07-09A







	Plug-in Elbow
	Use to change the tube direction from One-touch fittings by 90°.
Applicable tube O.D. [inch]	Model
1/8	KQ2L01-99A
5/32	KQ2L03-99A
3/16	KQ2L05-99A
1/4	KQ2L07-99A
5/16	KQ2L09-99A
5/10	ITALE00 00/1
3/8	KQ2L11-99A










**Plug-in Reducer** 




tube O.D. [inch]	Applicable Fitting Size	Model
	5/32	KQ2R01-03A
1/8	3/16	KQ2R01-05A
	1/4	KQ2R01-07A
5/32	3/16	KQ2R03-05A
5/52	1/4	KQ2R03-07A
3/16	1/4	KQ2R05-07A
3/10	5/16	KQ2R05-09A
4/4	5/16	KQ2R07-09A
1/4	3/8	KQ2R07-11A
5/40	3/8	KQ2R09-11A
5/16	1/2	KQ2R09-13A
3/8	1/2	KQ2R11-13A

	He Head M	exagon Socket ale Connector
	si tiy h	nternal hexagon ocket allows ghtening with a exagon wrench in onfined spaces.
Applicable tube O.D. [inch]	Connecting Thread	Model
1/8	10-32 UNF	KQ2S01-32□
	10-32 UNF	KQ2S03-32□
5/32	1/16	KQ2S03-33¤S
	1/8	KQ2S03-34 - S
3/16	1/8	KQ2S05-34□S
	10-32 UNF	KQ2S07-32□
	1/16	KQ2S07-33¤S
1/4	1/8	KQ2S07-34¤S
	1/4	KQ2S07-35¤S
	3/8	KQ2S07-36¤S
	1/8	KQ2S09-34 - S
5/16	1/4	KQ2S09-35 🗆 S
	3/8	KQ2S09-36 🗆 S
	1/8	KQ2S11-34 🗆 S
3/8	1/4	KQ2S11-35 🛛 S
0/0	3/8	KQ2S11-36⊤S



1/2










Applicable tube O.D. [inch]	Connecting Thread	Model
	10-32 UNF	KQ2T01-32 🛛
1/8	1/16	KQ2T01-33 - S
170	1/8	KQ2T01-34
	1/4	KQ2T01-35 - S
	10-32 UNF	KQ2T03-32 🗆
5/32	1/16	KQ2T03-33  S
5/52	1/8	KQ2T03-34
	1/4	KQ2T03-35¤S
3/16	1/8	KQ2T05-34¤S
5/10	1/4	KQ2T05-35¤S
	10-32 UNF	KQ2T07-32 🛛
	1/16	KQ2T07-33 DS
1/4	1/8	KQ2T07-34
	1/4	KQ2T07-35 DS
	3/8	KQ2T07-36
	1/8	KQ2T09-34  S
5/16	1/4	KQ2T09-35 S
	3/8	KQ2T09-36  S
	1/8	KQ2T11-34
2/9	1/4	KQ2T11-35 S
3/8	3/8	KQ2T11-36 - S
	1/2	KQ2T11-37 □S
	1/4	KQ2T13-35  S
1/2	3/8	KQ2T13-36 - S
	1/2	KQ2T13-37 □S













Easy 🔿 -Insertion Quick C Disconnect

New


**Engineered Anchor O**Grip Seal







### Different Diameter Union "Y"


5	Use to connect tubing for branching with size reduced
tube h] B	Model
/32	KQ2U01-03A
1/4	KQ2U01-07A
/16	KQ2U03-05A
1/4	KQ2U03-07A
1/4	KQ2U05-07A
6/16	KQ2U07-09A
3/8	KQ2U07-11A
3/8	KQ2U09-11A
1/2	KQ2U09-13A
1/2	KQ2U11-13A












KQ 2VS	Univers	k Socket Head sal Male Elbow lexagon socket n the top allows ghtening with a exagon wrench n confined paces.
Applicable tube O.D. [inch]	Connecting Thread	Model
1/8	10-32 UNF	KQ2VS01-32□
1/0	1/8	KQ2VS01-34 S
5/32	10-32 UNF	KQ2VS03-32
5/32	1/8	KQ2VS03-34¤S
3/16	1/8	KQ2VS05-34 S
	10-32 UNF	KQ2VS07-32□
1/4	1/8	KQ2VS07-34¤S
	1/4	KQ2VS07-35¤S
	1/8	KQ2VS09-34¤S
5/16	1/4	KQ2VS09-35 S
	3/8	KQ2VS09-36¤S
3/8	1/4	KQ2VS11-35¤S
0/0	3/8	KQ2VS11-36¤S
	2/0	KO0V642.26-0

1/2 3/8 KQ2VS

For Complete KQ2 Listing and Information: www.smcusa.com/kq2 For 3D CAD Information: www.smcusa.com/cad



	Extende	ed Male Elbow
	for int oth	e with male elbow fittings to avoid erferring with each her by making the bing multi-level.
Applicable tube O.D. [inch]	Connecting Thread	Model
	10-32 UNF	KQ2W01-32 🛛
1/8	1/16	KQ2W01-33 S
1/0	1/8	KQ2W01-34  S
	1/4	KQ2W01-35 S
	10-32 UNF	KQ2W03-32 🛛
5/32	1/16	KQ2W03-33 - S
5/32	1/8	KQ2W03-34  S
	1/4	KQ2W03-35¤S
3/16	1/8	KQ2W05-34 <sup>D</sup> S
3/10	1/4	KQ2W05-35 S
	10-32 UNF	KQ2W07-32 🗆
	1/16	KQ2W07-33
1/4	1/8	KQ2W07-34
	1/4	KQ2W07-35
	3/8	KQ2W07-36 □S
	1/8	KQ2W09-34  S
5/16	1/4	KQ2W09-35 S
	3/8	KQ2W09-36 - S
	1/4	KQ2W11-35□S
3/8	3/8	KQ2W11-36□S
	1/2	KQ2W11-37□S
	1/4	KQ2W13-35□S
1/2	3/8	KQ2W13-36□S
	1/2	KQ2W13-37□S



Applicable tube O.D. [inch]	Connecting Thread	Model
1/8	10-32 UNF	KQ2Y01-32□
	1/16	KQ2Y01-33□S
1/0	1/8	KQ2Y01-34 S
	1/4	KQ2Y01-35¤S
	10-32 UNF	KQ2Y03-32□
5/32	1/16	KQ2Y03-33¤S
5/52	1/8	KQ2Y03-34¤S
	1/4	KQ2Y03-35¤S
3/16	1/8	KQ2Y05-34¤S
5/10	1/4	KQ2Y05-35¤S
	10-32 UNF	KQ2Y07-32 🛛
	1/16	KQ2Y07-33 S
1/4	1/8	KQ2Y07-34
	1/4	KQ2Y07-35 S
	3/8	KQ2Y07-36  S
	1/8	KQ2Y09-34 S
5/16	1/4	KQ2Y09-35¤S
	3/8	KQ2Y09-36□S
	1/4	KQ2Y11-35□S
3/8	3/8	KQ2Y11-36□S
	1/2	KQ2Y11-37□S
	1/4	KQ2Y13-35□S
1/2	3/8	KQ2Y13-36□S
	1/2	KQ2Y13-37□S

0	Diffe	erent Diameter Plug-in "Y"
KQ2X	C	se to branch ne-touch fittings ith size reduced.
_		
Applicable tube O.D. [inch]	Applicable fitting size	Model
tube O.D.		Model KQ2X01-03A
tube O.D. [inch]	fitting size 5/32 3/16	KQ2X01-03A KQ2X03-05A
tube O.D. [inch] 1/8 5/32	fitting size 5/32 3/16 1/4	KQ2X01-03A KQ2X03-05A KQ2X03-07A
tube O.D. [inch] 1/8	fitting size 5/32 3/16	KQ2X01-03A KQ2X03-05A

### **Branch Universa** Male Elbow



1/4

5/16

3/8

1/2

Hexagon head o the body allows tightening with a box wrench. Use for branch

connections 10-32 UNF KQ2Z03-32 5/32 1/8 KC 10-32 UNF K 1/8 KQ2Z07 1/4 1/8 KQ2Z09-3 1/4 KQ2Z09-3

 1/4
 KQ2Z11-35
 S

 3/8
 KQ2Z11-36
 1

3/8 KQ2Z13-36 1/2 KQ2Z13-3

#### Double Branch Line

0	Universal Male Elbow		
a ri		se to four-branch female thread at ght angles. wo individual arts rotate 360°	
Applicable tube O.D. [inch]	Connecting Thread	Model	
1/8	1/8	KQ2ZD01-34  S	
5/32	1/8	KQ2ZD03-34	
3/16	1/8	KQ2ZD05-34	
1/4	1/8	KQ2ZD07-34  S	
	1/4	KQ2ZD07-35  S	
	3/8	KQ2ZD07-36	
5/16	1/4	KQ2ZD09-35  S	
	3/8	KQ2ZD09-36	
	1/2	KQ2ZD09-37  S	
3/8	1/4	KQ2ZD11-35	
	3/8	KQ2ZD11-36	
	1/2	KQ2ZD11-37 DS	
1/2	3/8	KQ2ZD13-36 □S	
	1/2	KQ2ZD13-37 DS	

### Triple Branch Universal Male Elbow

		Male Elbow	
	a riy in	se to six-branch female thread at ght angles. Three dividual parts otate 360°.	
Applicable tube O.D. [inch]	Connecting Thread	Model	
1/8	1/8	KQ2ZT01-34 -S	
5/32	1/8	KQ2ZT03-34	
3/16	1/8	KQ2ZT05-34	
1/4	1/8	KQ2ZT07-34	
	1/4	KQ2ZT07-35  S	
	3/8	KQ2ZT07-36	
5/16	1/4	KQ2ZT09-35 - S	
	3/8	KQ2ZT09-36 - S	
	1/2	KQ2ZT09-37 □S	
3/8	1/4	KQ2ZT11-35  S	
	3/8	KQ2ZT11-36  S	
	1/2	KQ2ZT11-37  S	
1/2	3/8	KQ2ZT13-36  S	
	1/2	KQ2ZT13-37	

NPO246-B AS-RRD-4.2M