

Speed Controller with One-touch Fittings, Standard Type

Elbow type



Model

AS12□1F
AS12□1F
AS22□1F
AS32□1F
AS42□1F

Port size
in the cylinder side

M 3
M 5
1/8, 1/4
1/4, 3/8
1/2

Applicable tubing O.D.

Metric size (mm)

Inch size (inch)

Applicable cylinder
bore size
(mm)

Page

Universal type



AS13□1F
AS13□1F
AS23□1F
AS33□1F
AS43□1F

M 3
M 5
1/8, 1/4
1/4, 3/8
1/2

Flame Resistant
(Equivalent to UL-94 Standard V-0)
Elbow type

AS22□1F
AS32□1F
AS42□1F

1/8, 1/4
1/4, 3/8
1/2

Elbow type
(Metal body)

AS12□1
AS22□1
AS22□1
AS32□1
AS42□1

M 5
1/8
1/4
3/8
1/2

In-line type



AS1001F
AS2001F
AS2051F
AS3001F
AS4001F

In-line type
Panel mount type

AS1001F
AS2001F
AS2051F
AS3001F
AS4001F

Dual speed
controller

ASD230F
ASD330F
ASD430F
ASD530F
ASD530F
ASD630F

M 5
1/8
1/4
1/4
3/8
1/2

Elbow type with Uni
One-touch fitting

AS22□1F
AS32□1F
AS42□1F

1/8, 1/4
3/8
1/2

Universal type with Uni
One-touch fitting

AS23□1F
AS33□1F
AS43□1F

1/8, 1/4
3/8
1/2

416

423

427

430

434

438

445

Speed Controller Standard Type		Model	Port size in the cylinder side	Port size on piping side													Applicable cylinder bore size (mm)	Page
				M3	M5	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2				
	Elbow type (Metal body)	AS12□0	M 3/M 5	●	●											ø2.5 to ø6	452	
		AS1400	M 3	●												ø6 to ø20		
		AS22□0	1/8, 1/4			●	●									ø20 to ø40		
		AS32□0	1/4, 3/8				●	●								ø40 to ø63		
		AS42□0	1/2						●							ø63 to ø100		
	In-line type	AS1000	M 3/M 5	●	●											ø2.5 to ø25	456	
		AS2000	1/8, 1/4			●	●									ø20 to ø40		
		AS3000	1/4, 3/8				●	●								ø32 to ø63		
		AS4000	1/4, 3/8, 1/2				●	●	●							ø40 to ø100		
		AS5000	1/4, 3/8, 1/2				●	●	●	●						ø40 to ø100		
	Large flow In-line type	AS420	1/4, 3/8, 1/2				●	●	●							ø63 to ø125	460	
		AS500	3/4							●						ø140 to ø200		
		AS600	1								●					ø160 to ø250		
		AS800	1 1/4									●				ø300		
		AS900	1 1/2, 2										●	●		ø300		
	In-line Push Locking type	AS3500	1/4, 3/8				●	●								ø32 to ø63	462	

Speed Controller with Residual Pressure Release Valve	Applicable tubing O.D.															Page	
	Model	Port size in the cylinder side	Metric size (mm)						Inch size (inch)						Applicable cylinder bore size (mm)		
			3.2	4	6	8	10	12	1/8	5/32	3/16	1/4	5/16	3/8			1/2
	AS22□1FE	1/8		●	●	●	●	●								ø20 to ø32	464
	AS22□1FE	1/4		●	●	●	●	●								ø20 to ø40	
	AS32□1FE	3/8			●	●	●	●								ø40 to ø63	
	AS42□1FE	1/2					●	●								ø63 to ø100	
	AS23□1FE	1/8		●	●	●	●	●								ø20 to ø32	464
	AS23□1FE	1/4		●	●	●	●	●								ø20 to ø40	
	AS33□1FE	3/8			●	●	●	●								ø40 to ø63	
	AS43□1FE	1/2					●	●								ø63 to ø100	
	AS2000E	1/8			●											ø20 to ø32	468
	AS2000E	1/4				●										ø20 to ø40	
	AS3000E	1/4				●										ø32 to ø63	
	AS3000E	3/8					●									ø32 to ø63	
	AS4000E	1/4					●									ø40 to ø100	
	AS4000E	3/8						●								ø40 to ø100	
	AS4000E	1/2							●							ø40 to ø100	

AS
ASP
ASN
AQ
ASV
AK
VCHC
ASS
ASR
ASQ
KE
TMH

Speed Controller Stainless Steel Series			Applicable tubing O.D.												Applicable cylinder bore size (mm)	Page																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
		Model	Port size in the cylinder side	Metric size (mm)						Inch size (inch)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
				3.2	4	6	8	10	12	1/8	5/32	3/16	1/4	5/16			3/8	1/2																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
Elbow type		AS12□1FG	M 5	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

				Applicable tubing O.D.														Applicable cylinder bore size (mm)	Page	
				Metric size (mm)						Inch size (inch)										
				Port size in the cylinder side	3.2	4	6	8	10	12	1/8	5/32	3/16	1/4	5/16	3/8	1/2			
Elbow type		Model	AS12□1FM	M 5	•	•	•	•	•	•	•	•	•	•	•	•	•	ø6 to ø20	494	
		AS22□1FM	1/8	•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø32		
		AS22□1FM	1/4	•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø40		
Universal type		Model	AS13□1FM	M 5	•	•	•	•	•	•	•	•	•	•	•	•	•	ø6 to ø20	494	
		AS23□1FM	1/8	•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø32		
		AS23□1FM	1/4	•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø40		
In-line type		Model	AS1001FM		•	•	•	•	•	•	•	•	•	•	•	•	•	ø6 to ø20	502	
		AS2001FM		•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø32		
		AS2051FM		•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø40		
Dual speed controller		Model	ASD230FM	M 5	•	•	•	•	•	•	•	•	•	•	•	•	•	ø6 to ø20	505	
		ASD330FM	1/8	•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø32		
		ASD430FM	1/4	•	•	•	•	•	•	•	•	•	•	•	•	•	•	ø20 to ø40		
Standard type (Metal body)					Port size on piping side															
		Model	AS12□0M-M5	M 5	M3	M5	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2			ø6 to ø20	499	
		AS22□0M-01	1/8				•											ø20 to ø32		
		AS22□0M-02	1/4					•										ø20 to ø40		

Series Variations

Speed Controller Adjustable by Flat Head Screwdriver

Elbow type



Model	Port size in the cylinder side
AS12□1F-D	M 5
AS22□1F-D	1/8, 1/4
AS32□1F-D	1/4, 3/8
AS42□1F-D	1/2

Universal type



Model	Port size in the cylinder side
AS13□1F-D	M 5
AS23□1F-D	1/8, 1/4
AS33□1F-D	1/4, 3/8
AS43□1F-D	1/2

In-line type



Model	Port size in the cylinder side
AS1001F-D	
AS2001F-D	
AS2051F-D	
AS3001F-D	
AS4001F-D	

Dual speed controller



Model	Port size in the cylinder side
ASD230F-D	M 5
ASD330F-D	1/8
ASD430F-D	1/4
ASD530F-D	1/4
ASD530F-D	3/8
ASD630F-D	1/2

Standard type (Metal body)



Model	Port size in the cylinder side
AS12□0-D	M 5
AS22□0-D	1/8, 1/4
AS32□0-D	1/4, 3/8
AS42□0-D	1/2

Applicable tubing O.D.		Applicable cylinder bore size (mm)	Page
Metric size (mm)	Inch size (inch)		
3.2 4 6 8 10 12 1/8 5/32 3/16 1/4 5/16 3/8 1/2		ø6 to ø20	512
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	
		ø6 to ø20	518
		ø20 to ø32	
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	522
		ø6 to ø20	
		ø20 to ø32	
		ø20 to ø40	
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	

Port size on piping side		Applicable cylinder bore size (mm)	Page
M3 M5 1/8 1/4 3/8 1/2 3/4 1 1 1/4 1 1/2 2			
		ø6 to ø25	527
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	

Tamper Proof Speed Controller

Elbow type



Model	Port size in the cylinder side
AS12□1F-T	M 5
AS22□1F-T	1/8, 1/4
AS32□1F-T	1/4, 3/8
AS42□1F-T	1/2

Universal type




Model	Port size in the cylinder side
AS13□1F-T	M 5
AS23□1F-T	1/8, 1/4
AS33□1F-T	1/4, 3/8
AS43□1F-T	1/2

In-line type



Model	Port size in the cylinder side
AS1001F-T	
AS2001F-T	
AS2051F-T	
AS3001F-T	
AS4001F-T	

Dual speed controller



Model	Port size in the cylinder side
ASD230F-T	M 5
ASD330F-T	1/8
ASD430F-T	1/4
ASD530F-T	1/4
ASD530F-T	3/8
ASD630F-T	1/2

Standard type (Metal body)



Model	Port size in the cylinder side
AS12□0-T	M 5
AS22□0-T	1/8, 1/4
AS32□0-T	1/4, 3/8
AS42□0-T	1/2

Applicable tubing O.D.		Applicable cylinder bore size (mm)	Page
Metric size (mm)	Inch size (inch)		
3.2 4 6 8 10 12 1/8 5/32 3/16 1/4 5/16 3/8 1/2		ø6 to ø20	530
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	
		ø6 to ø20	536
		ø20 to ø32	
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	539
		ø6 to ø20	
		ø20 to ø32	
		ø20 to ø40	
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	

Port size on piping side		Applicable cylinder bore size (mm)	Page
M3 M5 1/8 1/4 3/8 1/2 3/4 1 1 1/4 1 1/2 2			
		ø6 to ø25	544
		ø20 to ø40	
		ø40 to ø63	
		ø63 to ø100	

Check valve Series AK

Model	Port size	Page
AK2000	1/8, 1/4	562
AK4000	1/4, 3/8, 1/2	
AK6000	3/4, 1	

Bushing type check valve with One-touch fittings Straight type Male connector type Series AKH

Model	Port size	Page
AKH04	M5, 1/8	565
AKH06	M5, 1/8, 1/4	
AKH08	1/8, 1/4, 3/8	
AKH10	1/4, 3/8, 1/2	
AKH12	3/8, 1/2	

Bushing type Series AKB

Model	Port size	Page
AKB01	1/8	565
AKB02	1/4	
AKB03	3/8	
AKB04	1/2	

5.0 MPa check valve Series VCHC40

Model	Port size	Page
VCHC40	3/4, 1	571

Extension prevention system SSC valve

PAT. PEND.

Meter-out control type

Model	Port size	Page
ASS100	1/8	576
ASS300	1/4, 3/8	
ASS500	1/2, 3/4	
ASS600	3/4, 1	

Meter-in control type

Model	Port size	Page
ASS110	1/8	576
ASS310	1/4, 3/8	

Air saving valve Series ASR/ASQ

Pressure valve

Model	Port size	Page
ASR430F	1/4	581
ASR530F	1/4	
ASR630F	3/8	
ASR630F	3/8	

Flow valve

Model	Port size	Page
ASQ430F	1/4	581
ASQ530F	1/4	
ASQ530F	3/8	
ASQ630F	3/8	
ASQ630F	1/2	

AS

ASP

ASN

AQ

ASV

AK

VCHC

ASS

ASR

ASQ

KE

TMH