

Parallel Style Air Gripper: Wide Type

Series MHL2




Built-in dust-protection mechanism

A scraper with a dust lip is adopted for all rod rotating parts.

Double-end type oil-impregnated resin bearings with a metal backing are used for all shafts.

Fingers synchronized by a rack and pinion mechanism.



A large amount of gripping force is provided through the use of a double piston mechanism, while maintaining a compact design.

Smaller auto switch mountable

An auto switch can be mounted at 4 locations.

Stroke Variation

Model	Bore size mm			
	10	16	20	25
MHL2-□D	20	30	40	50
MHL2-□D1	40	60	80	100
MHL2-□D2	60	80	100	120

* Values of opening/closing strokes (mm)



MHZ

MHF

MHL

MHR

MHK

MHS

MHC

MHT

MHY

MHW

-X□

MRHQ

MA

D-□

Parallel Style Air Gripper: Wide Type

Series MHL2

ø10, ø16, ø20, ø25, ø32, ø40

How to Order

MHL 2-16 D -M9BW

Wide opening

Number of fingers

2	2 fingers
---	-----------

Bore size

10	10mm
16	16mm
20	20mm
25	25mm
32	32mm
40	40mm

Thread type

Symbol	Type	Cylinder bore
Nil	M thread	ø10 to 25
	Rc	ø32 to ø40
TN	NPT	
TF	G	

Action

D	Double acting
---	---------------

Made to Order
Refer to page 475 for details.

Number of auto switches

Nil	2 pcs.
S	1 pc.
n	"n" pcs.

Auto switch

Nil	Without auto switch (Built-in magnet)
-----	---------------------------------------

* For the applicable auto switch model, refer to the table below.

Opening/Closing stroke (mm)

Symbol	ø10	ø16	ø20	ø25	ø32	ø40
Nil	20	30	40	50	70	100
1	40	60	80	100	120	160
2	60	80	100	120	160	200

Applicable Auto Switch/Refer to pages 761 to 809 for further information on the auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length (m) *				Pre-wired connector	Applicable load	
							Electrical entry direction		0.5 (Nil)	1 (M)	3 (L)	5 (Z)			
					DC	AC	Perpendicular	In-line							
Solid state switch	—	Grommet	Yes	3-wire (NPN)	5V,12V	—	M9NV	M9N	●	●	●	○	○	IC circuit	Relay, PLC
				3-wire (PNP)			M9PV	M9P	●	●	●	○	○		
	2-wire			12V	M9BV		M9B	●	●	●	○	○	—		
	3-wire (NPN)			5V,12V	M9NWV		M9NW	●	●	●	○	○	IC circuit		
	3-wire (PNP)				M9PWV		M9PW	●	●	●	○	○			
	2-wire			12V	M9BWV		M9BW	●	●	●	○	○	—		
	3-wire (NPN)			5V,12V	M9NAV		M9NA	○	○	●	○	○	IC circuit		
	3-wire (PNP)				M9PAV		M9PA	○	○	●	○	○			
	2-wire			12V	M9BAV		M9BA	○	○	●	○	○	—		

* Lead wire length symbols: 0.5 m Nil (Example) M9NW
 1 m M (Example) M9NWM
 3 m L (Example) M9NWL
 5 m Z (Example) M9NWZ

* Solid state auto switches marked with "○" are produced upon receipt of order.

• Take note of hysteresis with 2-color indication type switches. Refer to "Auto Switch Hysteresis" on page 487.

Long stroke

One unit can handle workpieces with various diameters.


A large amount of gripping force is provided through the use of a double piston mechanism, while maintaining a compact design.

Double-end type oil-impregnated resin bearings with a metal backing are used for all shafts.


Built-in dust-protection mechanism

A high degree of freedom for mounting

Auto switch mountable



JIS Symbol



Made to Order

(Refer to pages 683 to 713 for details.)

Symbol	Specifications/Description
-X4	Heat resistance (100°C)
-X5	Fluororubber seal
-X28	With adjuster bolts for adjusting closing width
-X50	Without magnet
-X53	EPDM seal/Fluorine grease
-X63	Fluorine grease
-X79	Grease for food

Specifications

Bore size (mm)	10	16	20	25	32	40
Fluid	Air					
Action	Double acting					
Operating pressure (MPa)	0.15 to 0.6	0.1 to 0.6				
Ambient and fluid temperature	-10 to 60°C					
Repeatability	± 0.1					
Lubrication	Not required					
Effective gripping force (N) ^{Note)} at 0.5 MPa	14	45	74	131	228	396




Note) Gripping point = Bore size 10, 16, 20, 25: 40 mm, Bore size 32, 40: 80 mm.

Model/Stroke

Model	Bore size (mm)	Max. operating frequency c.p.m	Opening/Closing stroke (mm) (L2-L1)	Width at closing (mm) (L1)	Width at opening (mm) (L2)	Mass (g)
MHL2-10D	10	60	20	56	76	280
MHL2-10D1		40	40	78	118	345
MHL2-10D2			60	96	156	425
MHL2-16D	16	60	30	68	98	585
MHL2-16D1		40	60	110	170	795
MHL2-16D2			80	130	210	935
MHL2-20D	20	60	40	82	122	1025
MHL2-20D1		40	80	142	222	1495
MHL2-20D2			100	162	262	1690
MHL2-25D	25	60	50	100	150	1690
MHL2-25D1		40	100	182	282	2560
MHL2-25D2			120	200	320	2775
MHL2-32D	32	30	70	150	220	2905
MHL2-32D1		20	120	198	318	3820
MHL2-32D2			160	242	402	4655
MHL2-40D	40	30	100	188	288	5270
MHL2-40D1		20	160	246	406	6830
MHL2-40D2			200	286	486	7905



Note) The open and close time spans represent the value when the exterior of the workpiece is being held.



⚠ Precautions

- Be sure to read before handling.
- Refer to front matters 38 and 39 for Safety Instructions and pages 358 to 365 for Air Gripper and Auto Switch Precautions.


⚠ Warning

If a workpiece is hooked onto the attachment, make sure that excessive impact will not be created at the start and the end of the movement. Failure to observe this precaution may result in shifting or dropping the workpiece, which could be dangerous.

Series MHL2

Gripping Point


- The workpiece gripping point distance should be within the gripping force ranges given for each pressure in the effective gripping force graphs below.
- If operated with the workpiece gripping point beyond the indicated ranges, the load that will be applied to the fingers or the guide will become excessively unbalanced. As a result, the fingers could become loosened and adversely affect the service life of the unit.




R: Gripping position (mm)

Effective Gripping Force


- Indication of effective gripping force**
The gripping force shown in the tables represents the gripping force of one finger when all fingers and attachments are in contact with the work.
F = one finger thrust.




MHL2-10D




MHL2-10D₂




MHL2-16D




MHL2-16D₂




MHL2-20D




MHL2-20D₂




MHL2-25D




MHL2-25D₂




MHL2-32D




MHL2-32D₂




MHL2-40D



MHL2-40D₂



Model Selection Example



MHZ

MHF

MHL

MHR

MHK

MHS

MHC

MHT

MHY

MHW

-X□


MRHQ

MA

D-□

Series MHL2

Construction



Component Parts

No.	Description	Material	Note
1	Body	Aluminum alloy	Hard anodized
2	Finger	Aluminum alloy	Hard anodized
3	Piston rod	Stainless steel	
4	Rack	Stainless steel	
5	Pinion	Carbon steel	
6	Pinion cover	Carbon steel	Electroless nickel plated
7	Pinion axis	Stainless steel	Nitriding
8	Piston	Brass	
9	Piston A	Brass	
10	Piston B	Brass	
11	Piston A	Stainless steel	
12	Rod cover	Aluminum alloy	Chromate treated
13	Bumper	Urethane rubber	
14	Clip	Stainless steel spring wire	
15	Rubber magnet	Synthetic rubber	

No.	Description	Material	Note
16	Magnet	—	Nickel plated
17	Rod seal cover B	Cold rolled steel	Electroless nickel plated
18	Washer	Stainless steel	Nitriding
19	Bearing	Oil containing polyacetal with back metal	
20	Bearing	Oil containing polyacetal with back metal	
21	U nut	Carbon steel	Nickel plated
22	R-shape retaining ring	Carbon steel	Nickel plated
23	Type C retaining ring	Carbon steel	Nickel plated
24	Wave washer	Steel for spring	Phosphate coated
25	Conical spring washer	Carbon steel	Nickel plated

Replacement Parts

Description	MHL2-10□	MHL2-16□	MHL2-20□	MHL2-25□	MHL2-32□	MHL2-40□	Main parts
Seal kit	MHL10-PS	MHL16-PS	MHL20-PS	MHL25-PS	MHL32-PS	MHL40-PS	26/27/28/29/30
Piston assembly	MHL2-□□D	MHL-A1001	MHL-A1601	MHL-A2001	MHL-A2501	MHL-A3201	MHL-A4001
	MHL2-□□D1	MHL-A1002	MHL-A1602	MHL-A2002	MHL-A2502	MHL-A3202	MHL-A4002
	MHL2-□□D2	MHL-A1003	MHL-A1603	MHL-A2003	MHL-A2503	MHL-A3203	MHL-A4003
Rack	MHL2-□□D	MHL-A1004	MHL-A1604	MHL-A2004	MHL-A2504	MHL-A3204	MHL-A4004
	MHL2-□□D1	MHL-A1005	MHL-A1605	MHL-A2005	MHL-A2505	MHL-A3205	MHL-A4005
	MHL2-□□D2	MHL-A1006	MHL-A1606	MHL-A2006	MHL-A2506	MHL-A3206	MHL-A4006
Rod Cover assembly	MHL-A1007	MHL-A1607	MHL-A2007	MHL-A2507	MHL-A3207	MHL-A4007	29 <ø10>12/17/19/22/28 <ø16 to 40>12/13/17/19/22/28/29
Finger assembly	MHL-A1008	MHL-A1608	MHL-A2008	MHL-A2508	MHL-A3208	MHL-A4008	2/18/21/25
Pinion assembly	MHL-A1009	MHL-A1609	MHL-A2009	MHL-A2509	MHL-A3209	MHL-A4009	5/6/7/23/24





- * Order one finger assembly and pinion assembly per unit.
- * For piston assembly and rack, order 2 pieces per unit.
- * For rod cover assembly, order 4 pieces per unit.

Replacement part: grease pack part no.



MHL2-□□D (ø10 to 20)	GR-S-005 (5g)
MHL2-□□D (ø25, 32)	GR-S-010 (10g)
MHL2-□□D (ø40)	GR-S-020 (20g)
MHL2-□□D1 (ø10, 16)	GR-S-005 (5g)
MHL2-□□D1 (ø20, 25)	GR-S-010 (10g)
MHL2-□□D1 (ø32, 40)	GR-S-020 (20g)
MHL2-□□D2 (ø10, 16)	GR-S-005 (5g)
MHL2-□□D2 (ø20, 25)	GR-S-010 (10g)
MHL2-□□D2 (ø32, 40)	GR-S-010 (10g), GR-S-020 (20g) (1 pack each)

Dimensions

MHL2-10D□



* Dimensions of auto switch mounting groove (Enlarged view)



Model	A	B	C	D	E	F	G	H	J
MHL2-10D	38	36	51	26	56	76	100	24	80
MHL2-10D1	54	52	67	42	78	118	142	39	108
MHL2-10D2	72	70	85	60	96	156	180	57	146

Note 1) J dimension is at fully closed.
Note 2) D1 is different from D2 at finger closed because shaft is ejected from finger end. J dimension is different from the value which is subtracted stroke from G dimension.

MHZ

MHF

MHL

MHR

MHK

MHS

MHC

MHT

MHY

MHW

-X□

MRHQ




MA

D-□



Series **MHL2**

Dimensions

MHL2-16D□




* Dimensions of auto switch mounting groove (Enlarged view)



Model	A	B	C	D	E	F	G	H	J
MHL2-16D	40	45	60	28	68	98	128	26	98
MHL2-16D1	70	75	90	58	110	170	200	50	152
MHL2-16D2	90	95	110	78	130	210	240	70	192

Note 1) J dimension is at fully closed.
Note 2) D1 is different from D2 at finger closed because shaft is ejected from finger end. J dimension is different from the value which is subtracted stroke from G dimension.

MHL2-20D ☐



Note 1) J dimension is at fully closed.
Note 2) D1 is different from D2 at finger closed because shaft is ejected from finger end. J dimension is different from the value which is subtracted stroke from G dimension.





MA

D- ☐



Series **MHL2**

Dimensions

MHL2-25D□



* Dimensions of auto switch mounting groove (Enlarged view)



(mm)





Model	A	B	C	D	E	F	G	H	J
MHL2-25D	66	70	88	48	100	150	196	38	146
MHL2-25D1	120	124	142	102	182	282	328	86	244
MHL2-25D2	138	142	160	120	200	320	366	104	282

Note 1) J dimension is at fully closed.



Note 2) D1 is different from D2 at finger closed because shaft is ejected from finger end. J dimension is different from the value which is subtracted stroke from G dimension.

Dimensions

MHL2-32D□



* Dimensions of auto switch mounting groove (Enlarged view)



(mm)

Model	B	C	D	E	F	G	H	J
MHL2-32D	86	110	60	150	220	272	56	202
MHL2-32D1	134	158	108	198	318	370	104	282
MHL2-32D2	178	202	152	242	402	454	148	366

Note 1) J dimension is at fully closed.
Note 2) D1 is different from D2 at finger closed because shaft is ejected from finger end. J dimension is different from the value which is subtracted stroke from G dimension.

MHZ

MHF

MHL

MHR

MHK

MHS

MHC

MHT

MHY

MHW

-X□

MRHQ


MA

D-□

Series MHL2

Dimensions

MHL2-40D□



(mm)

Model	B	C	D	E	F	G	H	J
MHL2-40D	116	148	80	188	288	348	72	252
MHL2-40D1	174	206	138	246	406	466	130	370
MHL2-40D2	214	246	178	286	486	546	170	450

Note 1) J dimension is at fully closed.












Note 2) D1 is different from D2 at finger closed because shaft is ejected from finger end. J dimension is different from the value which is subtracted stroke from G dimension.

Series MHL2/Related Products

Auto Switch Installation Examples and Mounting Positions

Various auto switch applications are possible through different combinations of auto switch quantities and detecting positions.

1) Detection when Gripping Exterior of Workpiece

Detection example		1. Confirmation of fingers in reset position	2. Confirmation of workpiece held	3. Confirmation of workpiece released	
Position to be detected		Position of fingers fully opened 	Position when gripping a workpiece 	Position of fingers fully closed 	
Operation of auto switch		Auto switch turned ON when fingers return. (Light ON)	Auto switch turned ON when gripping a workpiece. (Light ON)	When a workpiece is not held (Abnormal operation): Auto switch to turn ON (Light illuminating)	
Detection combinations	One auto switch * One position, any of ①, ②, and ③, can be detected.	●	●	●	
	Two auto switches * Two positions of ①, ②, and ③ can be detected.	A	●	—	
		B	—	●	●
		C	●	—	●
How to determine auto switch installation position		Step 1) Fully open the fingers. 	Step 1) Position fingers for gripping a workpiece. 	Step 1) Fully close the fingers. 	
At no pressure or low pressure, connect the auto switch to a power supply, and follow the directions.		Step 2) Insert the auto switch into the auto switch installation groove in the direction shown in the following drawing. 			
Step 3) Slide the auto switch in the direction of the arrow until the indicator light illuminates. 		Step 3) Slide the auto switch in the direction of the arrow until the light illuminates and fasten it at a position 0.3 to 0.5 mm in the direction of the arrow beyond the position where the indicator light illuminates. In case of 2-color indicator type, fasten it at the location where the indicator light color changes from red to green.			
Step 4) Slide the auto switch further in the direction of the arrow until the indicator light goes out. 		Position where light turns ON 			
Step 5) Move the auto switch in the opposite direction and fasten it at a position 0.3 to 0.5 mm beyond the position where the indicator light illuminates. In case of 2-color indicator type, fasten it at the location when the indicator light color changes from red to green. Position where light turns ON 		Position to be secured 			
Position to be secured 		0.3 to 0.5 mm 			
0.3 to 0.5 mm 					

MHZ

MHF

MHL

MHR

MHK

MHS

MHC

MHT

MHY

MHW

-X□

MRHQ

MA

D-□









Note 1) It is recommended that gripping of a workpiece be performed close to the center of the finger stroke.
 Note 2) When holding a workpiece close at the end of open/close stroke of fingers, detecting performance of the combinations listed in the above table may be limited, depending on the hysteresis of an auto switch, etc.

Series MHL2/Related Products

Auto Switch Installation Examples and Mounting Positions

Various auto switch applications are possible through different combinations of auto switch quantities and detecting positions.

2) Detection when Gripping Interior of Workpiece


Detection example		1. Confirmation of fingers in reset position	2. Confirmation of workpiece held	3. Confirmation of workpiece released	
Position to be detected		Position of fingers fully closed 	Position when gripping a workpiece 	Position of fingers fully opened 	
Operation of auto switch		Auto switch turned ON when fingers return. (Light ON)	Auto switch turned ON when gripping a workpiece. (Light ON)	When a workpiece is not held (Abnormal operation): Auto switch to turn ON (Light illuminating)	
Detection combinations	One auto switch * One position, any of ①, ②, and ③, can be detected.	●	●	●	
	Two auto switches * Two positions of ①, ②, and ③ can be detected.	A	●	—	
		B	—	●	●
		C	●	—	●
How to determine auto switch installation position		Step 1) Fully close the fingers. 	Step 1) Position fingers for gripping a workpiece. 	Step 1) Fully open the fingers. 	
At no pressure or low pressure, connect the auto switch to a power supply, and follow the directions.		Step 2) Insert the auto switch into the auto switch installation groove in the direction shown in the following drawing. 			
Step 3) Slide auto switch in the direction of the arrow until the light illuminates and fasten it at a position 0.3 to 0.5 mm in the direction of the arrow beyond the position where the indicator light illuminates. In case of 2-color type, fasten it at the location where the indicator light color changes from red to green. Position where light turns ON  Position to be secured 		Step 3) Slide the auto switch in the direction of the arrow until the indicator light illuminates.  Step 4) Slide the auto switch a further distance in the direction of the arrow until the indicator light goes out.  Step 5) Move the auto switch in the opposite direction and fasten it at a position 0.3 to 0.5 mm beyond the position where the indicator light illuminates. In the case of 2-color indicator type, fasten it at the location when the indicator light color changes from red to green. Position where light turns ON  Position to be secured 			

Note 1) It is recommended that gripping of a workpiece be performed close to the center of the finger stroke.

Note 2) When holding a workpiece close at the end of open/close stroke of fingers, detecting performance of the combinations listed in the above table may be limited, depending on the hysteresis of an auto switch, etc.

Auto Switch Mounting

- (1) To set the auto switch, insert the auto switch into the installation groove of the cylinder as shown below and set it roughly.
- (2) Insert the auto switch into the auto switch bracket installation groove.
- (3) After confirming the detecting position, tighten the set screws (M2.5) attached to the auto switch and set it.
- (4) Be sure to change the detecting position in the state of (2).




Note) Use a watchmaker's screwdriver with a grip diameter of 5 to 6 mm to tighten the set screws (M2.5).
The tightening torque should be 0.05 to 0.1 N·m.
As a rule, it should be turned about 90° beyond the point at which tightening can be felt.

Auto Switch Mounting Bracket: Part No.

Auto switch part no.	Auto switch mounting bracket part no.
D-M9□(V) D-M9□W(V) D-M9□A(V)L	BMG2-012

Auto Switch Hysteresis


The auto switch hysteresis is shown in the table below.
Please refer to the table as a guide when setting auto switch positions.



Auto switch part no. Air gripper model	D-Y59□/Y69□/Y7P/Y7PV D-Y7□W/Y7□WV	D-M9□(V) D-M9□W(V) D-M9□A(V)L
	(mm)	
MHL2-10D□	0.8	0.3
MHL2-16D□	0.5	0.4
MHL2-20D□	0.5	0.7
MHL2-25D□	0.5	0.6
MHL2-32D□	0.5	0.6
MHL2-40D□	0.5	0.9

Auto Switch Mounting Brackets: Precautions

When auto switch is set on the mounting side as shown below, allow at least 2 mm run off space on mounting plate since the auto switch is protruded from the gripper edge.



MHZ

MHF

MHL

MHR

MHK

MHS

MHC

MHT

MHY

MHW

-X□

MRHQ

MA

D-□



Series MHL Specific Product Precautions


Be sure to read before handling.

Mounting Air Grippers/Series MHL2

Possible to mount from 2 directions.


Axial Mounting

- Body tapped




Model	Applicable bolts	Max. tightening torque (N·m)	Max. screw-in depth (mm)
MHL2-10D□	M4 x 0.7	2.1	8
MHL2-16D□	M5 x 0.8	4.3	10
MHL2-20D□	M6 x 1	7.3	12
MHL2-25D□	M8 x 1.25	17.7	16
MHL2-32D□	M8 x 1.25	18	16
MHL2-40D□	M10 x 1.5	36	20

- Body ø10 to ø25



Model	Applicable bolts	Max. tightening torque (N·m)
MHL2-10D□	M4 x 0.7	2.1
MHL2-16D□	M5 x 0.8	4.3
MHL2-20D□	M6 x 1	7.3
MHL2-25D□	M8 x 1.25	17.7

Lateral mounting



Model	Applicable bolts	Max. tightening torque (N·m)	Max. screw-in depth (mm)
MHL2-10D□	M4 x 0.7	1.4	5
MHL2-16D□	M5 x 0.8	2.8	7
MHL2-20D□	M6 x 1	4.8	7
MHL2-25D□	M8 x 1.25	12.0	7
MHL2-32D□	M8 x 1.25	12.0	11
MHL2-40D□	M10 x 1.5	24.0	12

How to Mount the Attachment to the Finger

- (1) Make sure that the piston rod is retracted so as not to apply undue strain on the piston rod while an attachment is being mounted to the finger.
- (2) Do not scratch or dent the sliding portion of the piston rod. Damage to the bearings or seals may cause air leaks or faulty operation.
- (3) Refer to the table below for the proper tightening torque on the bolt used for securing the attachment to the finger.

Model	Applicable bolts	Max. tightening torque (N·m)
MHL2-10D□	M4 x 0.7	1.4
MHL2-16D□	M5 x 0.8	2.8
MHL2-20D□	M6 x 1	4.8
MHL2-25D□	M8 x 1.25	12.0
MHL2-32D□	M10 x 1.5	24.0
MHL2-40D□	M12 x 1.75	42.2

