

# **2107 SERIES**

115V/220V

#### **MODELS**

2107VA20 2107VD20



#### **FEATURES**

- Oil-less operation
- Permanently lubricated bearings
- Stainless steel valves and lapped aluminum valve plates
- Die-cast aluminum heads and diaphragm hold down plates
- Balanced for smooth, low vibration operation
- Long-life diaphragms
- Field service capability
- 115 volt UL recognized motor and thermal protector
- Inlet filter
- Service Kit 650126

Declaration documentation for applicable models available upon request

Consult factory for custom applications

Thomas Division is an ISO 9001 registered company



## 2107 Series Performance Data

| MODEL NUMBER                             |   | 2107VA20                        |  | 2107VD20                 |  |
|--|---|---------------------------------|--|--------------------------|--|
| HEAD CONFIGURATION                       |   | Vacuum                          |  | Vacuum                   |  |
| STROKE                                   |   | .200 inches                     |  | .200 inches              |  |
| VACUUM                                   |   | Flow @ 115v                     |  | Flow @ 220v              |  |
| cfm @ in. Hg                             | I/min @ mbar (gauge)                      |                                 |  |                          |  |
| in. Hg                                   | mbar (gauge)                              | cfm                             | l/min                                      | cfm                      | l/min                                      |
| 0<br>5<br>10<br>15<br>20<br>25           | 0<br>-100<br>-200<br>-400<br>-600<br>-800 | .85<br>.65<br>.49<br>.33<br>.20 | 24.1<br>20.7<br>17.6<br>12.2<br>7.3<br>3.0 | .72<br>.56<br>.42<br>.29 | 20.4<br>17.7<br>15.1<br>10.6<br>6.4<br>2.4 |
| MAX. VACUUM                              |   | 28.2" in. Hg                    | -956 mbar                                  | 28.3" in. Hg             | -959 mbar                                  |
| MAX. AMBIENT AIR TEMP.                   |   | 104° F                          | 40(°C)                                     | 104° F                   | 40(°C)                                     |
| MIN. AMBIENT START TEMP.                 |   | 50° F                           | 10(°C)                                     | 50° F                    | 10(°C)                                     |
| MAX. RESTART VACUUM                      |   | 0" in. Hg                       | 0 mbar                                     | 0" in. Hg                | 0 mbar                                     |
| MOTOR VOLTAGE/FREQUENCY                  |   | 115/60/1                        |  | 220/50/1                 |  |
| MOTOR TYPE                               |   | Shaded Pole                     |  | Shaded Pole              |  |
| CURRENT AT RATED LOAD (AMPS)             |   | 2.2A                            |  | .7A                      |  |
| POWER AT RATED LOAD (WATTS)              |   | 142W                            |  | 91W                      |  |
| STARTING CURRENT<br>(LOCKED ROTOR, AMPS) |   | 4.0A                            |  | 1.3A                     |  |
| MIN. FULL LOAD SPEED (RPM)               |   | 1700 rpm                        |  | 1420 rpm                 |  |
| THERMAL PROTECTOR                        |   | Yes                             |  | Yes                      |  |
| NET WEIGHT                               |   | 6.3 lb.                         | 2.8 (kg)                                   | 6.3 lb.                  | 2.8 (kg)                                   |

The information presented in this material is based on technical data and test results of nominal units. It is believed to be accurate and reliable and is offered as an aid to help in the selection of Thomas products. It is the responsibility of the user to determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith. Thomas Products does not warrant, guarantee or assume any obligation or liability in connection with this information.

**NOTE:** Models pictured are representative of the series and do not represent a specific model number. Consult factory for detailed physical description.

### 2107VA20, 2107VD20







